



## Specifications Noxion LED Downlight Apollo V2.0 6-12W 690-1460lm 60D - 830/840 CCT | 145mm - Cutout 120mm

[View Product](#)

### General Information

|                          |                                                                                         |
|--------------------------|-----------------------------------------------------------------------------------------|
| SKU                      | 248323                                                                                  |
| EAN                      | 8719157046374                                                                           |
| Manufacturer Code        | 8719157046374                                                                           |
| Brand                    | Noxion                                                                                  |
| Manufacturer Name        | Noxion LED Downlight Apollo V2.0 6/9/12W MAX 1460lm 2CCT Cutout Ø120mm Frame Ø145mm Alu |
| Any Lamp all-in warranty | 6 Years                                                                                 |
| Average Lifetime (h)     | 100000                                                                                  |

### Technical Information

|                             |                                  |
|-----------------------------|----------------------------------|
| Tiltable                    | No                               |
| Technology                  | LED Integrated                   |
| Replaces (Watt)             | 24                               |
| Wattage                     | 12W                              |
| Voltage (V)                 | 220-240                          |
| Dimmable                    | Not Dimmable                     |
| Colour Code                 | 830 Warm White, 840 Cool White   |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                            |
| Colour of Light             | White                            |
| Light colour options        | CCT                              |

|                       |                                |
|-----------------------|--------------------------------|
| Beam Angle (degree)   | 60                             |
| Luminous Flux (Lumen) | 1460lm                         |
| Lumen per watt        | 126                            |
| Power factor          | >0.90                          |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PC (Polycarbonate)             |
| Finish of Reflector   | Aluminium                      |
| Product Type Category | LED Downlight                  |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 120                           |
| IP-Rating              | IP20                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Operating Temperature  | -20 to +40                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Colour of material     | White                         |
| Fixture Connection     | PI [Push-in connector 2-pole] |
| Series                 | Apollo                        |

## Dimensions

Height (mm)

**Why Any-lamp?**

92

Diameter (mm)

145



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

Type of sensor

No Sensor

